

DXO mounts are suitable for very heavy presses. These mounts are also customized to cover the complete base area of the machine. These mounts provides high shock isolation.



S. NO.	MODEL	Length (L) mm	Width (B) mm	Height (H) mm	Max. Load Capacity (Kg/pc)	Natural Frequency at Max. Load (Hz)
1	DXO-1	550	550	190	50,000	7
2	DXO-2	800	550	190	70,000	7
3	DXO-3	1100	550	190	90,000	7

Technical Specifications of Dhs1 Insulation Plate

S. No.	Properties	Values
1	Load (Kg/sq. cm)	05-20
2	Natural Frequency (Hz)	06-12
3	Thickness (mm)	65
4	Coefficient of Friction	0.8
5	Shore A Hardness	80-82
6	Working Temp. Range (Degree celcius)	-20 to +70
7	Oil & Chemical Resistance	Resistant to fuels, lubricating oils, cutting oils, water & ozone
8	Construction	Composite material made from nitrile rubber, cork particles & polyster fiber. The composite

Technical Specifications of Dhs3 Insulation Plate

S. No.	Properties	Values
1	Load (Kg/sq. cm)	04-28
2	Natural Frequency (Hz)	07-15
3	Thickness (mm)	50
4	Coefficient of Friction	0.8
5	Shore A Hardness	90-92
6	Working Temp. Range (Degree celcius)	-20 to +70
7	Oil & Chemical Resistance	Resistant to fuels, lubricating oils, cutting oils, water & ozone
8	Construction	Composite material made from nitrile rubber, cork particles & polyster fiber. The composite

