



S. NO.	MODEL	Load (Kg)	Free Height (mm)	Height Under Load (mm)	Bolt (G)	Top Plate (AxB) (mm)	Bottom Plate (Cx D) (mm)	Mounting Center Distance (CC) (mm)	Natural Frequency range (Hz)
1	MBI-E2-RSTD	62	115	95	M16	290x100	290x100	270	5.0-10
2	MBI-F2-RSTD	122	115	95	M16	290x100	290x100	270	3.0-8.0
3	MBI-G1-RSTD	218	115	95	M16	290x100	290x100	270	5.0-10
4	MBI-G5-RSTD	314	115	95	M16	290x100	290x100	270	5.0-10
5	MBI-H2-RSTD	420	115	95	M16	290x100	290x100	270	3.5-10
6	MBI-J2-RSTD	600	115	95	M16	290x100	290x100	270	3.5-11
7	MBI-K6-RSTD	1700	115	109	M16	290x100	290x100	270	5.0-10
8	MBI-L4-RSTD	1000	115	95	M16	290x100	290x100	270	3.5-11
9	MBI-N5-RSTD	2400	115	95	M16	290x100	290x100	270	5.0-10
10	MBI-P4-RSTD	2800	115	106	M16	290x100	290x100	270	5.0-8.0
11	MBI-P5-RSTD	1800	115	96	M16	290x100	290x100	270	5.0-10
12	MBI-V2-RSTD	4000	221	201	M16	380x150	380x150	350	5.0-10
13	MBI-Y2-RSTD	6000	261	241	M16	380x150	380x150	350	5.0-10