


ANTI-VIBRATION TABLE- ELASTOMERIC VIBRATION ISOLATION WITH GRANITE ISOLATED PAYLOAD AREA IN GRANITE TABLETOP, SERIES DIT-E-GPG





Dynemech Anti-Vibration Table Series DIT-E-GPG is suitable for all types of measuring and testing equipment used in the labs and clean rooms. These tables have a levelling adjustable leg. By rotating the nut, the level of the granite top can be maintained using precision spirit level/electronic level gauge. The top is made from a heavy granite slab which ensures rigidity and keeps the system stable and ensures lower natural frequency and high damping efficiency. The flatness accuracy of these granites is of grade '0' or '00' depending upon the application. The top surface of the granite slab is velvet finish to ensure smooth and lustrous finish.

The frame of the table is made from the structural steel having grade IS 2062. Powder coating on the frame is done to maintain corrosion free service life of the table. The vibration is achieved at 2 stages. The first stage is in the legs where the anti-vibration pads are assembled in the levelling leg which damps medium to high frequency vibrations. The second level of vibration isolation is achieved by DP1 layer of special profiled vibration insulation plates. This stack of the vibration insulation plate is tuned to low natural frequency and damps most of the incoming vibrations above 15-20 Hz. The isolated area is separated from the outer area and is supported in dependently from the ground. Any disturbance to the outer area will not affect the readings in the isolated area. Optional sturdy castor wheels are also provided for heavy versions for easy relocation of the table. Keyboard, CPU and monitor stands,. Drawers and cabinets can also be accommodated in these tables as per the application requirements.

These tables undergo a modern manufacturing process and rigorous testing before being supplied to customers. The entire process is carried out in our dedicated inhouse facility.

APPLICATIONS:

- Precision Instruments: Balances, Galvanometers, Electronic Microscopes, Atomic Absorption Spectrophotometers
- Laboratories: Chemical analysis, food sample testing, scientific research
- Industries: Pharmaceuticals, Food and Beverage, Chemicals
- Semiconductor Manufacturing: Precision and accuracy in R&D
- Weighing Experiments: High-precision balances and measuring instruments
- Scientific Applications: Metrology Equipment, Thermogravimetric Analysis (TGA), Digital Hardness Testers, HighResolution Microscopes, Surface Roughness Testers

SI. No.	Model	Load (Kg.)	Length (mm)	Width (mm)	Height at mean position (mm)	Granite Table Top Thickness (mm)	Natural Frequency (Hz)
1.	DIT-E-GPG-01	upto 250	500	500	800-1000	80	7-8
2.	DIT-E-GPG-01/s1	upto 250	630	630	800-1000	80	7-8
3.	DIT-E-GPG-02	upto 450	750	500	800-1000	80	7-8
4.	DIT-E-GPG-03	upto1250	900	600	800-1000	100	7-8
5.	DIT-E-GPG-04	upto 1250	1000	800	800-1000	150	7-8
6.	DIT-E-GPG-05	upto 1250	1200	1000	800-1000	150	7-8
7.	DIT-E-GPG-06	upto 1500	1800	1500	800-1000	150	7-8

OTHER TECHNICAL SPECIFICATIONS:-

A. Elastomeric Legs Specificarions

1	Levelling	with the help of bottom DLM mounts.
2	Height Adjustment	8mm
3	Vibration Isolation Efficiency	65-70 %