




Dynemech Jackup mpunts provides isolation solutions for various machines mounting conditions. The Dynemech jackup mounts also provides for high machine leveling capabilities. These jackup mounts provide high load capacity and best level stability. The bottom design provides for non-skid properties for the jackup mount the jackup mount also provide very good passive vibration isolation.

Applications : Machine Tools, Textile Machine, Graphics machines, Planners long bedded machines etc.

S. NO.	Model	Load Capacity Kg/pc	Height (H) (mm)	Dia (D) (mm)	Bolt (mm)	HEX (SW) (mm)	Temperature range (°C)	Levelling Adjustment
1	DJM0-B-u-FG-RD	850	49	90	M20X2.5(Length 38mm)	46	From -16 to 90	18
2	DJM1-B-u-FG-RD	1500	49	120	M20X2.5(Length 38mm)	46	From -16 to 90	18
3	DJM2-B-u-FG-RD	2500	49	160	M20X2.5(Length 38mm)	62	From -16 to 90	18
4	DJM0-B-m-FG-RD	440	49	90	M20X2.5(Length 38mm)	46	From -16 to 90	18
5	DJM1-B-m-FG-RD	860	49	120	M20X2.5(Length 38mm)	46	From -16 to 90	18
6	DJM2-B-m-FG-RD	1680	49	160	M20X2.5(Length 38mm)	62	From -16 to 90	18
7	DJM0-B-i-FG-RD	610	59	90	M20X2.5(Length 38mm)	46	From -16 to 90	18
8	DJM1-B-i-FG-RD	1210	59	120	M20X2.5(Length 38mm)	46	From -16 to 90	18
9	DJM2-B-i-FG-RD	2310	59	160	M20X2.5(Length 38mm)	62	From -16 to 90	18

NOTE : Please mention type of socket required at the time of ordering.