



Dynemech DLC series mounts are simple and effective vibration dampers for machines with respective holes in the base. These mounts offer both low frequency attenuation and stable machine levelling.

Note :- Bolts are also available in Big Hex Head Bolt, Small hex head Bolt.

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Standard Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-u-M12x1.75x100-B-Z-GR	150	65	30	M12X100	+3	M10/12/16/20	0.9	18	From -16 to 90	Dark Grey/Green	Applications: Tool Room Machines, Plastic Injection Moulding Machines, Pressure Die Casting Machines, Shaper, Printing and Textile Machines etc.
DLC2-u-M12x1.75x100-B-Z-GR	350	98	37	M12X100	+4	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC3-u-M16x2.0x100-B-Z-GR	600	125	44	M16X100	+4	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC4-u-M16x2.0x100-B-Z-GR	900	150	46	M16X100	+5	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC5-u-M18x2.5x150-B-Z-GR	1400	180	48	M18X150	+5	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC6-u-M20x2.5x150-B-Z-GR	1900	204	52	M20X150	+6	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC7-u-M20x2.5x150-B-Z-GR	2500	235	57	M20X150	+6	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC8-u-M24x3.0x200-B-Z-GR	3500	270	72	M24X200	+9	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC9-u-M24x3.0x200-B-Z-GR	4200	302	84	M24X200	+9	M10/12/16/20/24	0.9	18	From -16 to 90	Dark Grey/Green	
DLC1-u-10-M12x1.75x100-B-Z-GR	150	65	25	M12X100	+3	M10/12/16/20	0.9	25	From -16 to 90	Dark Grey/Green	Applications: Tool Room Machines, Plastic Injection Moulding Machines, Pressure Die Casting Machines, Shaper, Printing and Textile Machines etc.
DLC2-u-10-M12x1.75x100-B-Z-GR	350	98	32	M12X100	+4	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC3-u-10-M16x2.0x100-B-Z-GR	600	125	39	M16X100	+4	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC4-u-10-M16x2.0x100-B-Z-GR	900	150	41	M16X100	+5	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC5-u-10-M18x2.5x150-B-Z-GR	1400	180	43	M18X150	+5	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC6-u-10-M20x2.5x150-B-Z-GR	1900	204	47	M20X150	+6	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC7-u-10-M20x2.5x150-B-Z-GR	2500	235	52	M20X150	+6	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC8-u-10-M24x3.0x200-B-Z-GR	3500	270	67	M24X200	+9	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC9-u-10-M24x3.0x200-B-Z-GR	4200	302	79	M24X200	+9	M10/12/16/20/24	0.9	25	From -16 to 90	Dark Grey/Green	
DLC1-u-12-M12x1.75x100-B-Z-GR	150	65	27	M12X100	+3	M10/12/16/20	0.9	20	From -16 to 90	Dark Grey/Green	Applications: Tool Room Machines, Plastic Injection Moulding Machines, Pressure Die Casting Machines, Shaper, Printing and Textile Machines etc.
DLC2-u-12-M12x1.75x100-B-Z-GR	350	98	34	M12X100	+4	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	
DLC3-u-12-M16x2.0x100-B-Z-GR	600	125	41	M16X100	+4	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	
DLC4-u-12-M16x2.0x100-B-Z-GR	900	150	43	M16X100	+5	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	
DLC5-u-12-M18x2.5x150-B-Z-GR	1400	180	45	M18X150	+5	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	
DLC6-u-12-M20x2.5x150-B-Z-GR	1900	204	49	M20X150	+6	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	
DLC7-u-12-M20x2.5x150-B-Z-GR	2500	235	54	M20X150	+6	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	
DLC8-u-12-M24x3.0x200-B-Z-GR	3500	270	69	M24X200	+9	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	
DLC9-u-12-M24x3.0x200-B-Z-GR	4200	302	81	M24X200	+9	M10/12/16/20/24	0.9	20	From -16 to 90	Dark Grey/Green	



DLC1



DLC3



DLC5





DLC7



DLC9

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-m-M12x1.75x100-B-Z-GR	190	65	30	M12X100	+3	M10/12/16/20	0.7	30	From -16 to 90	Dark Grey/Green	Applications: Power Presses, Stamping Machines, Shearing Machines, Punching Machines. For machines with high vertical impact.
DLC2-m-M12x1.75x100-B-Z-GR	450	98	37	M12X100	+4	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	
DLC3-m-M16x2.0x100-B-Z-GR	800	125	44	M16X100	+4	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	
DLC4-m-M16x2.0x100-B-Z-GR	1150	150	46	M16X100	+5	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	
DLC5-m-M18x2.5x150-B-Z-GR	1750	180	48	M18X150	+5	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	
DLC6-m-M20x2.5x150-B-Z-GR	2400	204	52	M20X150	+6	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	
DLC7-m-M20x2.5x150-B-Z-GR	3200	235	57	M20X150	+6	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	
DLC8-m-M24x3.0x200-B-Z-GR	4000	270	72	M24X200	+9	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	
DLC9-m-M24x3.0x200-B-Z-GR	5000	302	84	M24X200	+9	M10/12/16/20/24	0.7	30	From -16 to 90	Dark Grey/Green	



DLC1



DLC3



DLC5





DLC7



DLC9

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-i-M12x1.75x100-B-Z-GR	250	65	40	M12X100	+3	M10/12/16/20	0.8	7	From -16 to 90	Dark Grey/Green	Applications: Power Presses, Stamping Machines, Shearing Machines, Punching Machines. For machines with high vertical impact.
DLC2-i-M12x1.75x100-B-Z-GR	575	98	47	M12X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC3-i-M16x2.0x100-B-Z-GR	1000	125	54	M16X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC4-i-M16x2.0x100-B-Z-GR	1600	150	56	M16X100	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC5-i-M18x2.5x150-B-Z-GR	2300	180	58	M18X150	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC6-i-M20x2.5x150-B-Z-GR	3100	204	62	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC7-i-M20x2.5x150-B-Z-GR	4000	235	67	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC8-i-M24x3.0x200-B-Z-GR	5200	270	82	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC9-i-M24x3.0x200-B-Z-GR	6500	302	94	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	



DLC1



DLC3



DLC5





DLC7



DLC9

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-p1-M12x1.75x100-B-Z-GR	75	65	30	M12X100	+3	M10/12/16/20	0.8	7	From -16 to 90	Dark Grey/Green	Applications: Power Presses, Stamping Machines, Shearing Machines, Punching Machines. For machines with high vertical impact.
DLC2-p1-M12x1.75x100-B-Z-GR	175	98	37	M12X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC3-p1-M16x2.0x100-B-Z-GR	300	125	44	M16X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC4-p1-M16x2.0x100-B-Z-GR	500	150	46	M16X100	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC5-p1-M18x2.5x150-B-Z-GR	700	180	48	M18X150	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC6-p1-M20x2.5x150-B-Z-GR	950	204	52	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC7-p1-M20x2.5x150-B-Z-GR	1250	235	57	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC8-p1-M24x3.0x200-B-Z-GR	1500	270	72	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC9-p1-M24x3.0x200-B-Z-GR	1900	302	84	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC1-p2-M12x1.75x100-B-Z-GR	80	65	35	M12X100	+3	M10/12/16/20	0.8	12	From -16 to 90	Dark Grey/Green	Applications: Medium Presses, Punching Presses, Centreless Grinding Machines, Gear Shapers, High Speed Machines on upper floors.
DLC2-p2-M12x1.75x100-B-Z-GR	220	98	42	M12X100	+4	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC3-p2-M16x2.0x100-B-Z-GR	410	125	49	M16X100	+4	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC4-p2-M16x2.0x100-B-Z-GR	620	150	51	M16X100	+5	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC5-p2-M18x2.5x150-B-Z-GR	900	180	53	M18X150	+5	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC6-p2-M20x2.5x150-B-Z-GR	1200	204	57	M20X150	+6	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC7-p2-M20x2.5x150-B-Z-GR	1600	235	62	M20X150	+6	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC8-p2-M24x3.0x200-B-Z-GR	2000	270	77	M24X200	+9	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC9-p2-M24x3.0x200-B-Z-GR	2600	302	89	M24X200	+9	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC1-p3-M12x1.75x100-B-Z-GR	95	65	39	M12X100	+3	M10/12/16/20	0.8	7	From -16 to 90	Dark Grey/Green	Applications: Tool Room Machines on suspended Floors, Light Weight Presses, Compressors etc.
DLC2-p3-M12x1.75x100-B-Z-GR	270	98	46	M12X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC3-p3-M16x2.0x100-B-Z-GR	490	125	53	M16X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC4-p3-M16x2.0x100-B-Z-GR	740	150	55	M16X100	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC5-p3-M18x2.5x150-B-Z-GR	1060	180	57	M18X150	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC6-p3-M20x2.5x150-B-Z-GR	1400	204	61	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC7-p3-M20x2.5x150-B-Z-GR	1950	235	66	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC8-p3-M24x3.0x200-B-Z-GR	2400	270	81	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC9-p3-M24x3.0x200-B-Z-GR	3150	302	93	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	



DLC1



DLC3



DLC5





DLC7



DLC9

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-s1-M12x1.75x100-B-Z-GR	76	65	35	M12X100	+3	M10/12/16/20	0.8	15	From -16 to 90	Dark Grey/Green	Applications: Tool Room Machines, Plastic Injection Moulding Machines, Pressure Die Casting Machines, Shaper, Printing and Textile Machines etc.
DLC2-s1-M12x1.75x100-B-Z-GR	220	98	42	M12X100	+4	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC3-s1-M16x2.0x100-B-Z-GR	490	125	49	M16X100	+4	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC4-s1-M16x2.0x100-B-Z-GR	620	150	51	M16X100	+5	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC5-s1-M18x2.5x150-B-Z-GR	890	180	53	M18X150	+5	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC6-s1-M20x2.5x150-B-Z-GR	1190	204	57	M20X150	+6	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC7-s1-M20x2.5x150-B-Z-GR	1620	235	62	M20X150	+6	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC8-s1-M24x3.0x200-B-Z-GR	1990	270	77	M24X200	+9	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC9-s1-M24x3.0x200-B-Z-GR	2620	302	89	M24X200	+9	M10/12/16/20/24	0.8	15	From -16 to 90	Dark Grey/Green	
DLC1-s2-M12x1.75x100-B-Z-GR	125	65	40	M12X100	+3	M10/12/16/20	0.8	8	From -16 to 90	Dark Grey/Green	Applications: Power Presses, Stamping Machines, Shearing Machines, Punching Machines. For machines with high vertical impact.
DLC2-s2-M12x1.75x100-B-Z-GR	300	98	47	M12X100	+4	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	
DLC3-s2-M16x2.0x100-B-Z-GR	550	125	54	M16X100	+4	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	
DLC4-s2-M16x2.0x100-B-Z-GR	850	150	56	M16X100	+5	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	
DLC5-s2-M18x2.5x150-B-Z-GR	1250	180	58	M18X150	+5	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	
DLC6-s2-M20x2.5x150-B-Z-GR	1700	204	62	M20X150	+6	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	
DLC7-s2-M20x2.5x150-B-Z-GR	2200	235	67	M20X150	+6	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	
DLC8-s2-M24x3.0x200-B-Z-GR	2800	270	82	M24X200	+9	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	
DLC9-s2-M24x3.0x200-B-Z-GR	3500	302	94	M24X200	+9	M10/12/16/20/24	0.8	8	From -16 to 90	Dark Grey/Green	



DLC1



DLC3



DLC5





DLC7



DLC9

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-hs1-M12x1.75x100-B-Z-GR	300	65	80	M12X100	+3	M10/12/16/20	0.8	6	From -16 to 90	Dark Grey/Green	

DLC2-hs1-M12x1.75x100-B-Z-GR	880	98	87	M12X100	+4	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	Applications : Forging Hammers, Heavy Gen Sets, Heavy Industrial machines, Test Rigs, Heavy presses etc.
DLC3-hs1-M16x2.0x100-B-Z-GR	1630	125	94	M16X100	+4	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	
DLC4-hs1-M16x2.0x100-B-Z-GR	2450	150	96	M16X100	+5	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	
DLC5-hs1-M18x2.5x150-B-Z-GR	3530	180	98	M18X150	+5	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	
DLC6-hs1-M20x2.5x150-B-Z-GR	4750	204	102	M20X150	+6	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	
DLC7-hs1-M20x2.5x150-B-Z-GR	6470	235	107	M20X150	+6	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	
DLC8-hs1-M24x3.0x200-B-Z-GR	7950	270	122	M24X200	+9	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	
DLC9-hs1-M24x3.0x200-B-Z-GR	10450	302	134	M24X200	+9	M10/12/16/20/24	0.8	6	From -16 to 90	Dark Grey/Green	
DLC1-hs2-M12x1.75x100-B-Z-GR	120	65	80	M12X100	+3	M10/12/16/20	0.8	4	From -16 to 90	Dark Grey/Green	
DLC2-hs2-M12x1.75x100-B-Z-GR	350	98	87	M12X100	+4	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC3-hs2-M16x2.0x100-B-Z-GR	650	125	94	M16X100	+4	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC4-hs2-M16x2.0x100-B-Z-GR	980	150	96	M16X100	+5	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC5-hs2-M18x2.5x150-B-Z-GR	1410	180	98	M18X150	+5	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC6-hs2-M20x2.5x150-B-Z-GR	1900	204	102	M20X150	+6	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC7-hs2-M20x2.5x150-B-Z-GR	2590	235	107	M20X150	+6	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC8-hs2-M24x3.0x200-B-Z-GR	3180	270	122	M24X200	+9	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC9-hs2-M24x3.0x200-B-Z-GR	4180	302	134	M24X200	+9	M10/12/16/20/24	0.8	4	From -16 to 90	Dark Grey/Green	
DLC1-hs3-M12x1.75x100-B-Z-GR	430	65	65	M12X100	+3	M10/12/16/20	0.8	7	From -16 to 90	Dark Grey/Green	Applications : Forging Hammers, Heavy Gen Sets, Heavy Industrial machines, Test Rigs, Heavy presses etc.
DLC2-hs3-M12x1.75x100-B-Z-GR	1240	98	72	M12X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC3-hs3-M16x2.0x100-B-Z-GR	2290	125	79	M16X100	+4	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC4-hs3-M16x2.0x100-B-Z-GR	3440	150	81	M16X100	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC5-hs3-M18x2.5x150-B-Z-GR	4950	180	83	M18X150	+5	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC6-hs3-M20x2.5x150-B-Z-GR	6500	204	87	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC7-hs3-M20x2.5x150-B-Z-GR	9070	235	92	M20X150	+6	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC8-hs3-M24x3.0x200-B-Z-GR	11140	270	107	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC9-hs3-M24x3.0x200-B-Z-GR	17870	302	119	M24X200	+9	M10/12/16/20/24	0.8	7	From -16 to 90	Dark Grey/Green	
DLC1-hs4-M12x1.75x100-B-Z-GR	180	65	65	M12X100	+3	M10/12/16/20	0.8	5	From -16 to 90	Dark Grey/Green	Applications : Forging Hammers, Heavy Gen Sets, Heavy Industrial machines, Test Rigs, Heavy presses, crushers etc.
DLC2-hs4-M12x1.75x100-B-Z-GR	530	98	72	M12X100	+4	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC3-hs4-M16x2.0x100-B-Z-GR	980	125	79	M16X100	+4	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC4-hs4-M16x2.0x100-B-Z-GR	1470	150	81	M16X100	+5	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC5-hs4-M18x2.5x150-B-Z-GR	2120	180	83	M18X150	+5	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC6-hs4-M20x2.5x150-B-Z-GR	2850	204	87	M20X150	+6	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC7-hs4-M20x2.5x150-B-Z-GR	3880	235	92	M20X150	+6	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC8-hs4-M24x3.0x200-B-Z-GR	4770	270	107	M24X200	+9	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC9-hs4-M24x3.0x200-B-Z-GR	6270	302	119	M24X200	+9	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC1-hs5-M12x1.75x100-B-Z-GR	430	65	95	M12X100	+3	M10/12/16/20	0.8	5	From -16 to 90	Dark Grey/Green	Applications : Forging Hammers, Heavy Gen Sets, Heavy Industrial machines, Test Rigs, Heavy presses etc.
DLC2-hs5-M12x1.75x100-B-Z-GR	1240	98	102	M12X100	+4	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC3-hs5-M16x2.0x100-B-Z-GR	2290	125	109	M16X100	+4	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC4-hs5-M16x2.0x100-B-Z-GR	3440	150	111	M16X100	+5	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC5-hs5-M18x2.5x150-B-Z-GR	4950	180	113	M18X150	+5	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC6-hs5-M20x2.5x150-B-Z-GR	6500	204	117	M20X150	+6	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC7-hs5-M20x2.5x150-B-Z-GR	9070	235	122	M20X150	+6	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC8-hs5-M24x3.0x200-B-Z-GR	11140	270	137	M24X200	+9	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	
DLC9-hs5-M24x3.0x200-B-Z-GR	17870	302	149	M24X200	+9	M10/12/16/20/24	0.8	5	From -16 to 90	Dark Grey/Green	



DLC1



DLC3



DLC5





DLC7



DLC9

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-h-M12x1.75x100-B-Z-GR	2760	65	30	M12X100	+3	M10/12/16/20	0.6	45	From -16 to 90	Dark Grey/Green	Applications : Very Heavy and long bed machines, long machining centres, planners etc.
DLC2-h-M12x1.75x100-B-Z-GR	7980	98	37	M12X100	+4	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	
DLC3-h-M16x2.0x100-B-Z-GR	14700	125	44	M16X100	+4	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	
DLC4-h-M16x2.0x100-B-Z-GR	22080	150	46	M16X100	+5	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	
DLC5-h-M18x2.5x150-B-Z-GR	31800	180	48	M18X150	+5	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	
DLC6-h-M20x2.5x150-B-Z-GR	42840	204	52	M20X150	+6	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	
DLC7-h-M20x2.5x150-B-Z-GR	58200	235	57	M20X150	+6	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	
DLC8-h-M24x3.0x200-B-Z-GR	71580	270	72	M24X200	+9	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	
DLC9-h-M24x3.0x200-B-Z-GR	94140	302	84	M24X200	+9	M10/12/16/20/24	0.6	45	From -16 to 90	Dark Grey/Green	



DLC1



DLC3



DLC5





DLC7



DLC9

Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Levelling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-P2-G-05-M12x1.75x100-B-Z-GR	250	65	35	M12x100	+3	M10/12/16/20	0.8	12	From -16 to 90	Dark Grey/Green	
DLC2-P2-G-05-M12x1.75x100-B-Z-GR	575	98	42	M12x100	+4	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC3-P2-G-05-M16x2.0x100-B-Z-GR	1000	125	49	M16x100	+4	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC4-P2-G-05-M16x2.0x100-B-Z-GR	1600	150	51	M16x100	+5	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC5-P2-G-05-M18x2.5x150-B-Z-GR	2300	180	53	M18x150	+5	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC6-P2-G-05-M20x2.5x150-B-Z-GR	3100	204	57	M20x150	+6	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC7-P2-G-05-M20x2.5x150-B-Z-GR	4000	235	62	M20x150	+6	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC8-P2-G-05-M24x3.0x200-B-Z-GR	5200	270	77	M24x150	+9	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	
DLC9-P2-G-05-M24x3.0x200-B-Z-GR	6500	302	89	M24x150	+9	M10/12/16/20/24	0.8	12	From -16 to 90	Dark Grey/Green	



Model	Load Capacity Kg/pc	Diameter (D) mm	Height (H) mm	Bolt Size (mm)	Leveling Adjustment Range (mm)	Possible Bolts	Coeff. of Friction against Concrete	Natural Frequency at Max. Load (Hz)	Temperature Range (°C)	Color	Applications
DLC1-a2-M12x1.75x100-B-Z-GR	190	65	23	M12X100	+3/-3	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC2-a2-M12x1.75x100-B-Z-GR	450	98	29	M12X100	+4/-4	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC3-a2-M16x2.0x100-B-Z-GR	800	125	36	M16X100	+4/-4	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC4-a2-M16x2.0x100-B-Z-GR	1150	150	39	M16X100	+5/-5	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC5-a2-M18x2.5x150-B-Z-GR	1750	180	41	M18X150	+5/-5	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC6-a2-M20x2.5x150-B-Z-GR	2400	204	45	M20X150	+6/-6	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC7-a2-M20x2.5x150-B-Z-GR	3200	235	48	M20X150	+6/-6	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC8-a2-M24x3.0x200-B-Z-GR	3975	270	62	M24X200	+9/-9	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green
DLC9-a2-M24x3.0x200-B-Z-GR	4900	302	77	M24X200	+9/-9	Da2	8	0.9	45	From -16 to 90	Dark Grey/Green