



S. NO.	MODEL	Load (Kg)	Free Height (mm)	Height Under Load (mm)	Bolt (G)	Top Plate (AxB) (mm)	Bottom Plate (CxD) (mm)	Mounting Center Distance (CC) (mm)	Natural Frequency range (Hz)
1	MAI-E2-RSTD	31	115	95	M16	220x100	220x100	200	5.0-10
2	MAI-F2-RSTD	61	115	95	M16	220x100	220x100	200	3.0-8.0
3	MAI-G1-RSTD	109	115	95	M16	220x100	220x100	200	5.0-10
4	MAI-G5-RSTD	157	115	95	M16	220x100	220x100	200	5.0-10
5	MAI-H2-RSTD	210	115	95	M16	220x100	220x100	200	3.5-10
6	MAI-J2-RSTD	300	115	95	M16	220x100	220x100	200	3.5-11
7	MAI-K6-RSTD	850	115	109	M16	220x100	220x100	200	5.0-10
8	MAI-L4-RSTD	500	115	95	M16	220x100	220x100	200	3.5-11
9	MAI-N5-RSTD	1200	115	95	M16	220x100	220x100	200	5.0-10
10	MAI-P4-RSTD	1400	115	106	M16	220x100	220x100	200	5.0-8.0
11	MAI-P5-RSTD	900	115	96	M16	220x100	220x100	200	5.0-10
12	MAI-V2-RSTD	2000	221	201	M16	300x150	300x150	270	5.0-10
13	MAI-Y2-RSTD	3000	261	241	M16	300x150	300x150	270	5.0-10