

Chloroprene (Neoprene) Antivibration Sheets : DCN

CR or Chloroprene is a homo-polymer of chloroprene or chloro-butadiene. It has excellent mechanical and good abrasion properties even without reinforcing fibers and has a reasonable resilience in grades over 60° shore A. It displays good resistance to heat, ozone, and weathering and also gives good adhesion to metal. The recommended operating temperature range is between -40°C to +125° C. It has good resistance to organic hydrocarbons. We also offer flame retardant grades.



NEOPRENE RUBBER SHEETS - Commercial Grade

Code	Thickness	Specific Gravity	Hardness (+/-5)	Tensile Strength	Elongation at break	Abrasion	Compression Set at 70° C for 22 Hrs	Temperature Range	Oil swell in ASTM oil 903	Colour
	mm	gm/cm ³	Shore A	(min) Kg/cm ²	(min) %	mm ³ 10 N	%	° C		
DCN-4	4	1.45	60	40	250	-	45	-35 to +80	90%	Black
DCN-5	5	1.45	60	40	250	-	45	-35 to +80	90%	Black
DCN-15	15	1.45	60	40	250	-	45	-35 to +80	90%	Black
DCN-25	25	1.45	60	40	250	-	45	-35 to +80	90%	Black

Standard Length	10 Mtr
Standard Width	1.2 Mtr

Note	1. One side or both side smooth or fabric finish can be supplied.
	2. Specifications are subject to change without notice.